

Urbane II Cleanflush[™] Invisi II®

Sanitary Compartment - Ambulant Applications 4.5/3 litre Dual Flush Toilet Suite with Wall Faced Pan and Invisi Series II® Cistern





Combining universal design and rimless pan technology, the **Urbane II Cleanflush™** is a superior flushing system suitable for domestic and commercial applications. Incorporating several patented technologies: Caroma Flow Splitter™, Caroma Flow Balancer™ and Caroma Uni-Orbital® Connector, the Cleanflush pan is innovative and the next evolution in toilets. The Flow Splitter evenly flows water around the top of the bowl to meet at the Flow Balancer which directs the water powerfully into the sump, reducing the need for brush cleaning. The rimless pan is easy to clean and unlike traditional pan profiles, provides full visibility of any grime build up. Caroma Cleanflush™ provides a cleaner clean for peace of mind. The adjustable flush pipe is a new feature for the Invisi II system. If the pan inlet hole is higher than the flush pipe due to floor tiling height variations, the flush pipe can be raised by up to 25mm.

Reference must be made to AS 1428.1-2021 with current amendments to Important:

determine circulation space, grab rail and installation requirements. The dimensions in this sheet may change with amendments to the standard.

Urbane Cleanflush™ wall faced back inlet 4.5 litre full flush rimless pan. Pan:

Universal trap for S or P-trap installations. Traps:

Fully glazed 50mm back inlet for concealed cistern. Inlet:

Cisterns: Invisi II Cistern – suitable for inwall, under counter, induct and inceiling applications.

The inVogue Round Push Buttons and Access Plate (supplied separately) are available in 5 finishes: Chrome (C), Black (B), Brushed Brass (BB), Brushed Nickel

(BN) and Gunmetal Grey (GM). Code No.687071.

Buttons: Sold separately: See Section 4 - CARE BUTTONS for further details.

Seats: The inVogue soft close quick release thermoset toilet seat with GermGard®

Antibacterial Protection; a unique technology which kills harmful bacteria, is provided as standard with seat caps in Stainless Steel (SS). Optional seat caps are available in 3 finishes, Brushed Brass (BB), Black (B) or Gunmetal Grey (GM). Code No.254213.

its products. The right is therefore reserved to vary specifications without notice.

Installation: The installation of the toilet suite shall be in accordance with the normal minimum

drainline grade requirements in AS/NZS 3500.2.

All dimensions are in millimetres and are subject to normal manufacturing variations. Caroma pursues a policy of continuing improvement in design and performance of





Dimensions:

Colour:

Urbane II Cleanflush™ Invisi II 4.5/3 litre Wall Faced Toilet Suite with Back Inlet Pan, Internal Overflow Cistern and Seat Note: The projection requirements detailed on this with Stainless Steel Seat Caps: Code No. illustration are for wheel chair access only. Inwall/Under Counter/Induct/Inceiling with inVogue Soft Close Quick Release Seat 746280W Button options: see 6.15.1 * Reference must be made to the AS 1428.1-2021 Amd 1 to confirm installation requirements. Adjustable flush pipe included To increase cistern height use elevated 450 to 460 flush pipe kit Requirement (not supplied) Care buttons 400 Θ \bigcirc 15 <u>@</u> 06 Invisi Series II® cistern .25 to top of flush pipe 300 – 1100 requirement from 814 -984 480 to top of seat 415 Integrated flush pipe support adic 440 102 185 460 -350 Ġ. 0 00 0 D82 Concealed Recommended 90 setout Fixing Bracket 205 Note: All height dimensions to 60 - 120 range 70mm min. for button underside of pan, make allowance (up to 50mm sideways Uni-Orbital® connector and remote mounting box for mortar bedding adjustment)